


Diode Module

Description

- 1) A package of series of two diodes.
- 2) With high thermal conductivity DBC as the insulation.
- 3) Welding by vacuum welding technology, which provide high reliability.



Typical Application





AC converter, inverter and DC motor.

Absolute Maximum Ratings (Packaged into modules, unless otherwise specified, $T_{CASE}=25^{\circ}\text{C}$)

Parameter	Test Conditions	Symbol	Values				Unit
			12	16	18	20	
Operating junction temperature range		T_j	-40-150				°C
Storage temperature range		T_{stg}	-40-125				°C
Repetitive peak reverse voltage	$T_j=25^{\circ}\text{C}$	V_{RRM}	1200	1600	1800	2000	V
Non-repetitive peak reverse voltage	$T_j=25^{\circ}\text{C}$	V_{RSM}	1300	1700	1900	2100	V
Average forward current	$T_c=100^{\circ}\text{C}$	$I_{F(AV)}$	300				A
Peak forward surge current	$t_p=10\text{ms}, \sin 180^{\circ}$,	I_{FSM}	8400				A
I^2t value for fusing	$T_j=25^{\circ}\text{C}$	I^2t	352800				A^2s
Insulation voltage	A.C 50Hz(1s/1min)	V_{ISO}	3600/3000				V



Electrical Characteristics (Packaged into modules, unless otherwise specified, $T_{CASE}=25^{\circ}\text{C}$)

Parameter	Test Conditions	Symbol	Values	Unit
Peak forward voltage	$I_F=900\text{A}$, $t_P=380\mu\text{s}$	V_{FM}	≤ 1.6	V
Threshold voltage	$T_j=150^{\circ}\text{C}$	V_{TO}	≤ 0.81	V
Dynamic resistance	$T_j=150^{\circ}\text{C}$	R_d	≤ 0.9	$\text{m}\Omega$
Repetitive peak reverse current	$V_R=V_{RRM}$ $T_j = 25^{\circ}\text{C}$ $T_j = 150^{\circ}\text{C}$	I_{RRM1} I_{RRM2}	≤ 100 ≤ 90	μA mA
Thermal resistance(Per chip)	Junction to case Case to heatsink	$R_{th(j-c)}$ $R_{th(c-s)}$	0.13 0.05	$^{\circ}\text{C}/\text{W}$

Performance Curves
FIG.1: Forward characteristics(per diode)

FIG.2: Peak on-state surge current

FIG.3: Forward current vs. case temperature

FIG.4: Maximum transient thermal impedance


Mechanical Characteristics

Module size	115mm×50mm
Module height	53mm
Terminal distance of (1) /(2) /(3)	42.1mm/35mm/23.4mm
Mounting torque(M5)	5±15%Nm
Terminal torque(M8)	9±15%Nm



symbol