

Product Manual


EKWIN ELECTRONICS CO.,LTD

EK BTA08

www.ekwin.net


Standard TRIACS
BTA08 Serial
Main Features:

I_{T(RMS)}	V_{DRM/V_{RRM}}	V_{TM}
8 A	600v 800V	≤1.55 V

Description:


High current density due to double mesa technology; Glass Passivation.BTA0808series TRIACS is suitable for general purpose AC switching.they can be used as an ON/OFF Function in applications such as static relays,heating regulation,induction motor stating circuits..or for phase control operation light dimmers,motor speed controllers.

Absolute Ratings(limiting values) :

Symbol	Parameter		Value	Unit
T_{stg}	Storage junction temperature range		- 40 to + 150	°C
T_j	Operating junction temperature range		- 40 to + 125	°C
I_{T(RMS)}	RMS on-state current	TO-220F (TC=95°C)	8	A
		TO-220A(TC=100°C)		
I_{TSM}	Non repetitive surge peak on-state current (tp=10ms)		80	A
V_{DRM}	Repetitive peak off-state voltage(Tj =25°C)		600/800	V
V_{RRM}	Repetitive peak reverse voltage(Tj =25°C)		600/800	V
V_{DSM}	Non repetitive surge peak Off-state voltage		V _{DRM} + 100	V
V_{RSM}	Non repetitive peak reverse voltage		V _{RRM} + 100	V
I²t	I ² t value for fusing tp = 10 ms		32	A ² s
dI/dt	Critical rate of rise of on-state current (I _G =2×I _{GT})		50	A/μs

I_{GM}	Peak gate current	4	A
P_{G(AV)}	Average gate power dissipation	1	W
P_{GM}	Peak gate power	5	W

Electrical Characteristics : (T_j=25°C unless otherwise specified)

Symbol	Test Condition	Quadrant	Range	Value				Unit
				T	S	C	B	
I_{GT}	V _D =12V R _L =33Ω	I-II-III	MAX	5	10	35	50	mA
V_{GT}		I-II-III	MAX	1.5				V
V_{GD}	V _D =V _{DRM} R _L =3.3kΩ T _j =125°C	I-II-III	MIN	0.2				V
I_L	I _G =1.2 I _{GT}	I-III	MAX	15	20	50	70	mA
		II		25	35	60	80	
I_H	I _{TM} = 100mA		MAX	10	15	40	60	mA
dV/dt	V _D =2/3V _{DRM} Gate Open T _j =125°C		MIN	50	200	500	1000	V/μs

Static Characteristics

Symbol	Parameter		Value(MAX)			Unit
V_{TM}	I _{TM} =11A tp= 380μs		T _j =25°C			V
I_{DRM} I_{RRM}	V _D =V _{DRM} , V _R =V _{RRM}	T _j =25°C			5	
		T _j =125°C			1	

Thermal Resistances :

Symbol	Parameter		Value	Unit
R_{th(j-c)}	Junction to case for AC	TO-220A	4.0	°C/W
		TO-220F	4.6	

FIG.1: Maximum power dissipation versus RMS on-state current




FIG.3: Surge peak on-state current versus number of cycles




FIG.5: Non-repetitive surge peak on-state current for a sinusoidal pulse with width $t_p < 20\text{ms}$, and corresponding value of I^2t ($dI/dt < 50\text{A}/\mu\text{s}$)




FIG.2: RMS on-state current versus case temperature




FIG.4: On-state characteristics (maximum values)






FIG.6: Relative variations of gate trigger current, holding current and latching current versus junction temperature




Ordering Information:

BT	A	08 - 600	B
TRIAC SERIES			
A:insulated		IGT Class	
B:non-insulated			
$I_{T(RMS)}:8A$		$600:V_{DRM}/V_{RRM} \geq 600$	
		$800:V_{DRM}/V_{RRM} \geq 800$	

Package Mechanical Data :



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	4.40		4.60	0.173		0.181
B	0.61		0.88	0.024		0.035
C	0.46		0.70	0.018		0.028
C2	1.21		1.32	0.048		0.052
C3	2.40		2.72	0.094		0.107
D	8.60		9.70	0.339		0.382
E	9.60		10.4	0.378		0.409
F	6.20		6.60	0.244		0.260
G		2.54			0.1	
H	28.0		29.8	1.102		1.173
L1		3.75			0.148	
L2	1.14		1.70	0.045		0.067
L3	2.65		2.95	0.104		0.116
V1		45°			45°	



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	4.40		4.80	0.173		0.189
B	0.74	0.80	0.83	0.029	0.031	0.033
C	0.48		0.75	0.019		0.030
C2	2.40		2.70	0.094		0.106
C3	2.60		3.00	0.102		0.118
D	8.80		9.30	0.346		0.366
E	9.70		10.3	0.382		0.406
F	6.40		7.00	0.252		0.276
G		2.54			0.1	
H	28.0		29.8	1.102		1.173
L1		3.63			0.143	
L2	1.14		1.70	0.045		0.067
L3		3.30			0.130	
V1		45°				45°