

Product Manual

EKWIN ELECTRONICS CO.,LTD

EK BTA80

www.ekwin.net

Standard TRIACS

BTA80 Serial

Main Features:

$I_{T(RMS)}$	V_{DRM}/V_{RRM}	I_{GT1-3}
80 A	600/800/1200/1600 V	$\leq 50\text{mA}$

Description:



BTA80 triac provides good commutation capability, which is suitable for general purpose AC switching and voltage regulation, and can be used in static relays, heating regulation, induction motor starting circuits. From all three pins to external heatsink, BTA80 triac provides an insulation voltage of 2500 VRMS.

Absolute Ratings(limiting values) :

Symbol	Parameter		Value	Unit
T_{stg}	Storage junction temperature range		- 40 to + 150	°C
T_j	Operating junction temperature range		- 40 to + 125	°C
$I_{T(RMS)}$	RMS on-state current	TO-247S (TC=70°C)	80	A
I_{TSM}	Non repetitive surge peak on-state current (tp=10ms)		800	A
V_{DRM}	Repetitive peak off-state voltage($T_j = 25^\circ\text{C}$)		600/800/1200/1600	V
V_{RRM}	Repetitive peak reverse voltage($T_j = 25^\circ\text{C}$)		600/800/1200/1600	V
V_{DSM}	Non repetitive surge peak Off-state voltage		$V_{DRM} + 100$	V
V_{RSM}	Non repetitive peak reverse voltage		$V_{RRM} + 100$	V
I^2t	I^2t value for fusing tp = 10 ms		3200	A^2s
dI/dt	Critical rate of rise of on-state current ($I_G = 2 \times I_{GT}$)		100	$\text{A}/\mu\text{s}$

I_{GM}	Peak gate current	8	A
P_{G(AV)}	Average gate power dissipation	2	W
P_{GM}	Peak gate power	10	W

Electrical Characteristics : (T_j=25°C unless otherwise specified)

Symbol	Test Condition	Quadrant	Range	Value	Unit
I_{GT}	V _D =12V R _L =33Ω	I-II-III	MAX	50	mA
V_{GT}		I-II-III	MAX	1.3	V
V_{GD}	V _D =V _{DRM} R _L =3.3kΩ T _j =125°C	I-II-III	MIN	0.2	V
I_L	I _G =1.2 I _{GT}	I-III	MAX	80	mA
		II		120	
I_H	I _{TM} = 100mA		MAX	80	mA
dV/dt	V _D =2/3V _{DRM} Gate Open T _j =125°C		MIN	1500	V/μs

Static Characteristics

Symbol	Parameter	Value(MAX)	Unit
V_{TM}	I _{TM} =120A t _p = 380μs	T _j =25°C	1.6
I_{DRM} I_{RRM}	V _D =V _{DRM} , V _R =V _{RRM}	T _j =25°C	20
		T _j =125°C	10

Thermal Resistances :

Symbol	Parameter	Value	Unit
R_{th(j-c)}	Junction to case for AC ITO-247S(Ins)	0.35	°C/W

Fig.1: Maximum power dissipation versus RMS on-state current




Fig.3 : Surge peak on-state current versus number of cycles




Fig.5 : Non-repetitive surge peak on-state current for a sinusoidal pulse with width $t_p < 20\text{ms}$ and corresponding value of I_t ($dI/dt < 100\text{A}/\mu\text{s}$)




Fig.2 : RMS on-state current versus case temperature




Fig.4 : On-state characteristics (maximum values)






Fig.6: Relative variations of gate trigger current,holding current and latching current versus unclipping temperature



Ordering Information:

TRIAC SERIES	BT	A	80	-1200	600: $V_{DRM}/V_{RRM} \geq 600$ 800: $V_{DRM}/V_{RRM} \geq 800$ 1200: $V_{DRM}/V_{RRM} \geq 1200$ 1600: $V_{DRM}/V_{RRM} \geq 1600$
		A:insulated		$I_{T(RMS)}:80A$	

Package Mechanical Data :



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	19.7	19.9	20.1	0.776	0.783	0.791
B	26.9	27.1	27.3	1.059	1.067	1.075
C	19.4	19.9	20.4	0.764	0.783	0.803
D	3.80	3.90	4.00	0.150	0.154	0.157
E	2.56	2.66	2.76	0.101	0.105	0.109
F	1.66	1.76	1.86	0.065	0.069	0.073
G		5.45			0.215	
H	5.05	5.10	5.50	0.199	0.201	0.217
J	1.45	1.50	1.55	0.057	0.059	0.061
K	2.20	2.30	2.40	0.087	0.091	0.094
L	0.60	0.70	0.80	0.024	0.028	0.031
M	21.2	21.3	21.4	0.835	0.839	0.843
ØN	3.20	3.30	3.40	0.126	0.130	0.134

ITO-247